

Borough of Stanhope

CONSTRUCTION DEPARTMENT

77 Main Street Stanhope, NJ 07874

Tel: 973-347-0159 ext. 20 Fax: 973-347-6058

APPLICATION FOR CERTIFICATE OF HABITABILITY RESALE

FEE: \$125.00 EACH RESALE	
Property Location:	
Block / Lot:	
Number of bedrooms:	
Owner of Record:	
Owner Mailing Address:	
Owner Phone:	
Owner's Agent	
(If Applicable)	
Agent Phone:	
Name and address of person(s) to whom property is being SOLD:	
Fentative Closing Date:	
OFFICE USE ONLY	
Paid (date):	Amount \$
Check#	_Cash
Received by	Comments

\$125.00 each RESALE - CHECKS PAYABLE TO BOROUGH OF STANHOPE

ALL PARTITIONS EITHER PUT UP BY CURRENT OWNER OR PAST OWNER MUST BE REMOVED PRIOR TO CERTIFICATE BEING ISSUED.

Condominiums must provide copy of listing showing number of bedrooms

CERTIFICTE OF HABITABILITY RENTAL OR RESALE

- 1. SMOKE DETECTOR ON EACH FLOOR, INCLUDING BASEMENT
- 2. AT LEAST ONE CARBON MONOXIDE DETECTOR OUTSIDE A BEDROOM
- 3. ABC TYPE FIRE EXTINGUISHER NO LARGER THAN 10LBS WITHIN 10FT OF KITCHEN AREA.
- * IF A CONDO MUST SUBMIT COPY OF LISTING.

WHERE TO LOCATE SMOKE DETECTORS:

Detectors are to be located on every level of a residence, (basement, first floor, second floor) excluding crawl spaces and unfinished attics, and in every separate sleeping area, between sleeping areas and living areas such as the kitchen, garage, basement or utility room. In homes with only one sleeping area on one floor, a detector is to be placed in the hallway outside the bedroom as shown in Figure 1. In single floor homes with two separate sleeping areas, two detectors are required outside each sleeping area as shown in Figure 2. In multi-level homes, detectors are to be located outside sleeping areas and at every finished level of the home as shown in Figure 3. Basement level detectors are to be located in close proximity to the bottom of basement stairwells as shown in Figure 4.

WHERE NOT TO LOCATE SMOKE DETECTORS:

To avoid false alarms and/or improper operation, avoid installation of smoke detectors in the following areas:

Kitchens - smoke from cooking may cause a nuisance alarm

Bathrooms - excessive steam from a shower may cause a nuisance alarm

Near forced air ducts used for heating or air conditioning - air movement may prevent smoke from reaching detector

Near furnaces of any type - air and dust movement and normal combustion products may cause a nuisance alarm

The 4 inch "Dead Air" space where the ceiling meets the wall as shown in Figure 5

The peak of an "A" frame type ceiling - "Dead Air" at the top may prevent smoke from reaching the detector

CARBON MONOXIDE ALARMS are to be located in every separate sleeping area per NFPA 720 and manufacturer's recommendations.

FURTHER INFORMATION ON DETECTOR PLACEMENT:

For further information about smoke detector placement, consult National Fire Protection Association's Standard No. 74-1984, titled "Household Fire Warning Equipment." For carbon monoxide alarms, their publication is Recommended Practice No. 720. These publications may be obtained by writing to the Publication Sales Department, National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

